

HUBS 240S STRAIGHTPULL

Model	Hub axle system	Spoke holes	Color	Disc mount	Free wheel body	Technical data			Accessories
						Spoke hole ø [mm]	Optimized spoke ø [mm]	Weight ± 5% [g] ²⁾	
Product name	Built-in width [mm]								
240s non disc	5/100 mm RWS / Quick release 9/100 mm DT Swiss Thru bolt 15/100 mm Thru axle 15/110 mm PS ³⁾ Thru axle 20/110 mm Thru axle Lefty 5/130 mm RWS / Quick release 5/135 mm RWS / Quick release 5/145 mm RWS / Quick release 10/135 mm DT Swiss Thru bolt 12/135 mm Thru axle 12/142 mm Thru axle 12/150 mm Thru axle bolt on	20 holes 24 holes 28 holes 32 holes 36 holes 40 holes	Black White Polished	Center Lock® IS (6-bolt)	Shimano 9 / 10 / 11 and Sram 9 / 10 Shimano 11 Road ¹⁾ Campagnolo 9 / 10 / 11 Sram MTB XD 11	Spoke hole ø [mm] Optimized spoke ø [mm] Weight ± 5% [g] ²⁾		Center Lock® / IS (6-bolt) adapter	
240s non disc Front	100	●	●	●	○	2.5 2.0 107			
240s non disc Rear	130		●	●	○ ○	2.5 2.0 212			
240s Road db Center Lock®	5/100 mm RWS / Quick release 9/100 mm DT Swiss Thru bolt 15/100 mm Thru axle 15/110 mm PS ³⁾ Thru axle 20/110 mm Thru axle Lefty 5/130 mm RWS / Quick release 5/135 mm RWS / Quick release 5/145 mm RWS / Quick release 10/135 mm DT Swiss Thru bolt 12/135 mm Thru axle 12/142 mm Thru axle 12/150 mm Thru axle bolt on	20 holes 24 holes 28 holes 32 holes 36 holes 40 holes	Black White Polished	Center Lock® IS (6-bolt)	Shimano 9 / 10 / 11 and Sram 9 / 10 Shimano 11 Road ¹⁾ Campagnolo 9 / 10 / 11 Sram MTB XD 11	Spoke hole ø [mm] Optimized spoke ø [mm] Weight ± 5% [g] ²⁾		Center Lock® / IS (6-bolt) adapter	
240s Road db Center Lock® Front	100	○ ○ ●	● ●	● ○	○ ○	2.5 2.0 118			
240s Road db Center Lock® Rear	142		● ●	● ○	○ ● ○	2.5 2.0 220			
240s MTB db Center Lock®	5/100 mm RWS / Quick release 9/100 mm DT Swiss Thru bolt 15/100 mm Thru axle 15/110 mm PS ³⁾ Thru axle 20/110 mm Thru axle Lefty 5/130 mm RWS / Quick release 5/135 mm RWS / Quick release 5/145 mm RWS / Quick release 10/135 mm DT Swiss Thru bolt 12/135 mm Thru axle 12/142 mm Thru axle 12/150 mm Thru axle bolt on	20 holes 24 holes 28 holes 32 holes 36 holes 40 holes	Black White Polished	Center Lock® IS (6-bolt)	Shimano 9 / 10 / 11 and Sram 9 / 10 Shimano 11 Road ¹⁾ Campagnolo 9 / 10 / 11 Sram MTB XD 11	Spoke hole ø [mm] Optimized spoke ø [mm] Weight ± 5% [g] ²⁾		Center Lock® / IS (6-bolt) adapter	
240s MTB db Center Lock® Front	100	● ○ ○	●	● ○	○ ○	2.5 2.0 122			
240s MTB db Center Lock® Front Predictive Steering³⁾	100	○ ○ ●	●	● ○	○ ○	2.5 2.0 118			
240s MTB db Center Lock® Front Predictive Steering³⁾	110		●	● ○	○ ○	2.5 2.0 176			
240s MTB db Center Lock® Rear	135		●	● ○	● ○	2.5 2.0 231			
240s MTB db Center Lock® Rear	142		○	● ○	● ○	2.5 2.0 227			
240s MTB db Center Lock® Rear	142		○	● ○	● ○	2.5 2.0 216			
240s MTB db IS	5/100 mm RWS / Quick release 9/100 mm DT Swiss Thru bolt 15/100 mm Thru axle 15/110 mm PS ³⁾ Thru axle 20/110 mm Thru axle Lefty 5/130 mm RWS / Quick release 5/135 mm RWS / Quick release 5/145 mm RWS / Quick release 10/135 mm DT Swiss Thru bolt 12/135 mm Thru axle 12/142 mm Thru axle 12/150 mm Thru axle bolt on	20 holes 24 holes 28 holes 32 holes 36 holes 40 holes	Black White Polished	Center Lock® IS (6-bolt)	Shimano 9 / 10 / 11 and Sram 9 / 10 Shimano 11 Road ¹⁾ Campagnolo 9 / 10 / 11 Sram MTB XD 11	Spoke hole ø [mm] Optimized spoke ø [mm] Weight ± 5% [g] ²⁾		Center Lock® / IS (6-bolt) adapter	
240s MTB db IS Front	100	● ○ ○	●	●	○ ○	2.5 2.0 130			
240s MTB db IS Front	100	○ ○ ●	●	●	○ ○	2.5 2.0 127			
240s MTB db IS Front oversize	110	○ ○ ○ ●	●	●	○ ○	2.5 2.0 164			
240s MTB db IS Rear	135		●	● ●	○ ○	2.5 2.0 237			
240s MTB db IS Rear	142		○	● ●	○ ○	2.5 2.0 232			
240s MTB db IS Rear	142		○	● ○	● ○	2.5 2.0 222			
240s MTB db IS Rear	150		●	●	○ ○	2.5 2.0 276			

● = Standard

○ = Option

¹⁾ incl. washer for 10 speed

²⁾ Weight without CL adapter, Quick release or Thru axle

³⁾ Predictive Steering for RS-1

Model	Hub axle system											Spoke holes				Color			Disc mount		Free wheel body				Technical data			Accessories								
	Product name	Built-in width [mm]	5/100 mm RWS / Quick release	9/100 mm DT Swiss Thru bolt	15/100 mm Thru axle	15/110 mm PS ³⁾ Thru axle	20/110 mm Thru axle	Lefty	5/130 mm RWS / Quick release	5/135 mm RWS / Quick release	5/145 mm RWS / Quick release	10/135 mm DT Swiss Thru bolt	12/135 mm Thru axle	12/142 mm Thru axle	12/150 mm Thru axle	bolt on	20 holes	24 holes	28 holes	32 holes	36 holes	40 holes	Black	White	Polished	Center Lock®	IS (6-bolt)		Shimano 9 / 10 / 11 and Sram 9 / 10	Shimano 11 Road ¹⁾	Campagnolo 9 / 10 / 11	Sram MTB XD 11	Spoke hole ø [mm]	Optimized spoke ø [mm]	Weight ± 5% [g] ²⁾	Center Lock® / IS (6-bolt) adapter
240s non disc																																				
Front	100	●														●	●	●	●			●										2.4	2.0	105		
Rear	130							●									●	●	●			●					○	●	○	○	2.4	2.0	209			
	130							●									●	●	●			●					○	○	●	○	2.4	2.0	209			
240s Road db Center Lock®																																				
Front	100	○	○	●													●	●				●										2.5	2.0	126		
Rear	142								○		○	○	●				●	●	●			●					○	●		○	2.5	2.0	228			
240s MTB db Center Lock®																																				
Front fifteen	100	●	○	○														●	●			●										2.5	2.0	130		
	100	○	○	●														●	●			●										2.5	2.0	126		
Rear	135							●		○	○	○						●	●			●					●		○		2.5	2.0	233			
	142							○		○	○	●					●	●	●			●					○	○	●		2.5	2.0	218			
	142							○		○	○	●						●	●			●					●	○	●		2.5	2.0	228			
240s MTB db IS																																				
Front	100	●	○															●	●			●										2.5	2.0	145		
Front oversize	110	○	○	○	●													●				●										2.5	2.0	165		
Rear	135							●		○	○	○						●				●					●		○		2.5	2.0	244			
	142							○		○	○	●						●	●			●					●	●		○	2.5	2.0	240			
	142							○		○	○	●						●	●			●					●	○	●		2.5	2.0	230			
	150											●						●				●					●	●		○	2.5	2.0	275			
240s Lefty																																				
Front	Lefty							●									●	●	●			●										2.4	2.0	124		
240s single speed																																				
Rear	135							●										●				●										2.5	2.0	243		
	135											●						●				●										2.5	2.0	308		

● = Standard

○ = Option

¹⁾ incl. washer for 10 speed

²⁾ Weight without CL adapter, Quick release or Thru axle

³⁾ Predictive Steering for RS-1