

Model	Hub axle system	Spoke holes	Color	Disc mount	Free wheel body	Technical data			Accessories	
						Spoke hole ø [mm]	Optimized spoke ø [mm]	Weight ± 5% [g] <sup>2)</sup>		
<b>Product name</b>	<b>Built-in width [mm]</b>									
	5/100 mm RWS / Quick release									
	9/100 mm DT Swiss Thru bolt									
	15/100 mm Thru axle									
	15/110 mm PS <sup>3)</sup> Thru axle									
	20/110 mm Thru axle									
	Lefty									
	5/130 mm RWS / Quick release									
	5/135 mm RWS / Quick release									
	5/145 mm RWS / Quick release									
	10/135 mm DT Swiss Thru bolt									
	12/135 mm Thru axle									
	12/142 mm Thru axle									
	12/150 mm Thru axle									
	bolt on									
	20 holes									
	24 holes									
	28 holes									
	32 holes									
	36 holes									
	40 holes									
	Black									
	White									
	Polished									
	Center Lock®									
	IS (6-bolt)									
	Shimano 9 / 10 / 11 and Sram 9 / 10									
	Shimano 11 Road <sup>1)</sup>									
	Campagnolo 9 / 10 / 11									
	Sram MTB XD 11									
	Spoke hole ø [mm]									
	Optimized spoke ø [mm]									
	Weight ± 5% [g] <sup>2)</sup>									
	Center Lock® / IS (6-bolt) adapter									
<b>350 non disc</b>										
<b>Front</b>	100	●						2.5	2.0	110
<b>Rear</b>	130							2.5	2.0	264
<b>350 Road db Center Lock®</b>										
<b>Front</b>	100	○	●					2.5	2.0	136
<b>Rear</b>	142							2.5	2.0	244
<b>350 MTB db Center Lock®</b>										
<b>Front</b>	100	●						2.5	2.0	151
	100	○	●					2.5	2.0	130
<b>Rear</b>	135							2.5	2.0	271
	142							2.5	2.0	243
	142							2.5	2.0	267
<b>350 MTB db IS</b>										
<b>Front</b>	110							2.5	2.0	239
	100	●						2.5	2.0	160
	100	○	●					2.5	2.0	137
<b>Rear</b>	135							2.5	2.0	279
	142							2.5	2.0	274
	142							2.5	2.0	252

● = Standard

○ = Option

<sup>1)</sup> incl. washer for 10 speed

<sup>2)</sup> Weight without CL adapter, Quick release or Thru axle

<sup>3)</sup> Predictive Steering for RS-1

Model	Hub axle system											Spoke holes				Color			Disc mount		Free wheel body				Technical data			Accessories							
	Product name	Built-in width [mm]	5/100 mm RWS / Quick release	9/100 mm DT Swiss Thru bolt	15/100 mm Thru axle	15/110 mm PS <sup>3)</sup> Thru axle	20/110 mm Thru axle	Lefty	5/130 mm RWS / Quick release	5/135 mm RWS / Quick release	5/145 mm RWS / Quick release	10/135 mm DT Swiss Thru bolt	12/135 mm Thru axle	12/142 mm Thru axle	12/150 mm Thru axle	bolt on	20 holes	24 holes	28 holes	32 holes	36 holes	40 holes	Black	White	Polished	Center Lock®	IS (6-bolt)		Shimano 9 / 10 / 11 and Sram 9 / 10	Shimano 11 Road <sup>1)</sup>	Campagnolo 9 / 10 / 11	Sram MTB XD 11	Spoke hole ø [mm]	Optimized spoke ø [mm]	Weight ± 5% [g] <sup>2)</sup>
<b>350 non disc</b>																																			
<b>Front</b>	100	●																●	●			●										2.6	2.0	149	
<b>Rear</b>	130							●										●	●			●				○	●	○			2.6	2.0	265		
	130							●											●	●			●			○	○	●			2.6	2.0	252		
<b>350 Road db Center Lock®</b>																																			
<b>Front</b>	100	○		●													●	●	●			●			●	○						2.6	2.0	136	
<b>Rear</b>	142								○		○	○	●					●	●	●		●			●	○	○	●		○	2.6	2.0	267		
<b>350 MTB db Center Lock®</b>																																			
<b>Front</b>	100	●																						●	○						2.6	2.0	156		
	100	○		●																			●		●	○					2.6	2.0	136		
<b>Rear</b>	135							●		○	○	○										●		●	○	●		○			2.6	2.0	272		
	142							○		○	○	●										●		●	○	●		○			2.6	2.0	267		
	142							○		○	○	●										●		●	○	○	●				2.6	2.0	244		
<b>350 MTB db IS</b>																																			
<b>Front</b>	100	●																							●						2.6	2.0	194		
	100	○		●																				●		●					2.6	2.0	172		
	110					●																		●		●					2.6	2.0	239		
<b>Rear</b>	135							●		○	○	○										●		●	●		○			2.6	2.0	305			
	142							○		○	○	●										●		●	●		○			2.6	2.0	300			
	142							○		○	○	●						●	●	●		●		●	○	●				2.6	2.0	277			
	150														●							●		●	●		○			2.6	2.0	344			

● = Standard

○ = Option

<sup>1)</sup> incl. washer for 10 speed

<sup>2)</sup> Weight without CL adapter, Quick release or Thru axle

<sup>3)</sup> Predictive Steering for RS-1